



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	DC-26.5GHz
Dielectric Withstanding Voltage	1000V
VSWR	1.15 typ
Insertion Loss	$\leq 0.05 * \text{Sqrt}(f_GHz)$
Operating Temperature	- 55~+165 °C

Material & Coat-Plating

Inner Conductor	Brass, Gold
Dielectric	PTFE
Body/Nut	Stainless Steel, Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ±- ANGLES ±1°	APVD	Product Model SMA/2.92-JJ SMA Male to 2.92 Male Adaptor				
		PRODUCT SPEC					
		APPLICATION SPEC					
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO		
		CUSTOMER DRAWING		SCALE 4	SCALE 4: 1	SHEET1 OF 1	RVE 1