



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	5000 MΩ
Operating Frequency	10MHz-40GHz
Dielectric Withstanding Voltage	500V
VSWR	≤1.25
Insertion Loss	0.08* $\sqrt{f_GHz}$
Operating Temperature	- 55~+125℃
Inner Conductor	Beryllium copper gilding
Dielectric	PEI
Body	STAINLESS STEEL Passivtionof

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model 2.92-SSMP-JJG 2.92Male SSMP Male Connector			
		PRODUCT SPEC				
		APPLICATION SPEC	SIZE A4	GAGE CODE OT8L4	DRAWING NO	
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1
					SHEET 1 OF 1	RVE 1