

Solid State High Power Amplifier Systems

1-200MHz/53dB Gain/53dBm Psat/220V AC

Model: TLPA1M200M-53-53-BC

TLPA1M200M-53-53-BC is a solid state high power amplifier systems provides high output power and high gain across the 1 to 200MHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 1-200MHz
- Gain: 53dB Min
- Psat Output Power: 53dBm Min
- Protection: Over TEM, over voltage, over current ,infinite VSWR protection
- 50 Ohm Matched Input / Output



Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	1-200			MHz
Power Gain	GP	53			dB
Gain flatness	ΔGL			± 3	dB
Gain adjust Range	ΔGR		23		dB
Output Psat	Psat	53			dBm
Harmonics	HAM			-15	dBc
Input VSWR	VSWRin			1.3	:1
AC Voltage	Vac		220		V AC
Impedance	I/O-IMP	50			Ohms

Mechanical Specifications:



Parameter	Value	Units
Input /Output Connector	N Female/N Female	
Communication Connector	GPIO/LAN	
Size	500*480*212	mm

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	0 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



Key Features:

Parameter	Advantages
Control functions	1, Power setting On/Off 2, ALC automatic level control
Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Infinite VSWR
Remote control	RS422/Ethernet
Cooling system	Built in Cooling system, forced air cooling

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+40	°C
Non-operating Temperature*	-30		+50	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave, 3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA1M200M-53-53-BC	Solid State High Power Amplifier Systems 1-200MHz, Gain:53dB, Psat:53dBm, 220V AC, Built in Fan Cooling	Rev.1.1