

Coaxial High-pass Filter

500-2000 MHz/SMA Female

Model: TLHF-500M-2000M-L

TLHF-500M-2000M-L is a coaxial High-pass filter with a passband frequency from 500 to 2000 MHz and a rejection frequency from DC to 350 MHz. The maximum insertion loss of the filter is 1.5 dB and the minimum rejection is 30 dB.

Features:

- Passband Frequency Range 500 to 2000MHz
- Low Insertion Loss

Applications:

- Instrumentations
- Test Labs
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	500		2000	MHz
Passband Insertion Loss			1.5	dB
Pass Band Ripple			1.3	dB
VSWR			1.6	:1
Rejection@DC-350MHz	30			dB
Power Handling			2	W
Impedance	50			Ohms

Environmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40	mm

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLHF-500M-2000M-L	Coaxial High-pass Filter, Passband frequency range: 500-2000MHz, Passband Insertion Loss: 1.5dB, SMA Female Coaxial Fixed Termination	Rev.1.1