

Solid State High Power Amplifier Systems

3-30MHz/53dB Gain/53dBm Psat/220V AC

Model:TLPA3M30M-53-53-BC

TLPA3M30M-53-53-BC is a solid state high power amplifier systems provides high output power and high gain across the 3 to 30MHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 3-30MHz
- Gain: 53dB Min
- Psat Output Power: 53dBm Min
- Protection:Over TEM,over voltage, over current ,infinite VSWR protection
- 50 Ohm Matched Input / Output

Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	3-30			MHz
Power Gain	GP	53	55		dB
Gain flatness	ΔGL		± 2	± 3	dB
Output P1dB	P1dB		50		dBm
Output Psat	Psat	53	54		dBm
Spurious	Spur			-60	dBc
Harmonics	HAM		-15		dBc
Input VSWR	VSWRin		1.5	2	:1
AC Voltage	Vac	110	220		V AC
Power Consumption	Pdiss			800	W
Impedance	I/O-IMP	50			Ohms


Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	N Female/N Female	
Size	482.6*133.2*447	mm
Weight	≤25	Kg

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing: Unit:mm



Key Features:

Parameter	Advantages
Control functions	1, Power setting On/Off 2,ALC automatic level control
Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,infinite VSWR
Remote control	RS422/Ethernet
Cooling system	Built in Cooling system,forced air cooling

主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off 2, ALC automatic level control
内置保护功能 Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Infinite VSWR
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system, forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	°C
存储温度 Non-operating Temperature*	-30		+50	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave, 3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA3M30M-53-53-BC	Solid State High Power Amplifier Systems 3-30MHz, Gain:53dB, Psat:53dBm, 220V AC, Built in Fan Cooling	Rev.1.1