

Coaxial Band-pass Filter

125-250 MHz/SMA Female

Model: TLBF-125M-250M-L

TLBF-125M-250M-L is a coaxial band-pass filter with a passband frequency from 125 to 250 MHz and a rejection frequencies at $f_c \pm 100$ MHz. The maximum insertion loss of the filter is 1.8 dB and the minimum rejection is 40 dB.

Features:

- Passband Frequency Range 125 to 250 MHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	125		250	MHz
Band Width			125	MHz
Insertion Loss(f_0)			1.8	dB
Pass Band Ripple			1.6	dB
VSWR			1.6	:1
Rejection@ $f_c \pm 100$ MHz	40			dB
Power Handling			2	W
Impedance	50			Ohms

Environmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40.4	mm

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-125M-250M-L	Coaxial Band-pass Filter, Passband frequency range: 125-250MHz, Insertion Loss(f0): 1.8dB, SMA Female	Rev.1.0