

Coaxial Band-pass Filter

1460-1530 MHz/SMA Female

Model: TLBF-1460M-1530M-L

TLBF-1460M-1530M-L is a coaxial band-pass filter with a passband frequency from 1460 to 1530 MHz and a rejection frequencies from DC to 1400 MHz and point at 1590 MHz. The maximum insertion loss of the filter is 2.8 dB and the minimum rejection is 40 dB.

Features:

- Passband Frequency Range 1460 to 1530 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	1460		1530	MHz
Passband Insertion Loss			2.8	dB
Pass Band Ripple			2.6	dB
VSWR			1.6	:1
Rejection@DC-1400MHz&1590MHz	10			dB
Power Handling			2	W
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40.4	mm

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-1460M-1530M-L	Coaxial Band-pass Filter, Passband frequency range: 1460-1530MHz, Passband Insertion Loss: 2.8dB, SMA Female	Rev.1.0