泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

# Coax Directional Coupler

## 8-12GHz/10dB Coupling/SMA Female

## Model: TC-80120-10S

TC-80120-10S is a coaxial directional coupler that delivers a 10 dB nominal coupling level and 14 dB minimum directivity across the full frequency range from 8 to 12 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

### Features:

- Output Frequency:8-12GHz
- Coupling: 10dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

### Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

### Electrical Characteristics:

| Parameter | Min | Typ | Max | Units |
|---|---|---|---|---|
| Frequency Range | 8 | | 12 | GHz |
| Insertion Loss (Excl Coupling) | | 0.5 | 0.6 | dB |
| Coupling | | 10±1 | | dB |
| Directivity | 14 | 15 | | dB |
| Power Handling | | | 50 | W |
| VSWR | | | 1.4 | :1 |
| Impedance | | 50 | | Ohms |

### Mechanical Specifications:


| Parameter | Value | Units |
|---|---|---|
| Input/Output Connector | SMA Female/SMA Female | |
| Size | 33*15*14 | mm |

泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

## Outline Drawing:

Unit:mm; Tolerance:±0.1mm






ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## Environmental Conditions:


| Parameter | Min | Typ | Max | Units |
|---|---|---|---|---|
| Temperature Range | -45 | | +85 | ℃ |
| Relative humidity | 100% RH at 35c, 95%RH at 40℃ | | | % |
| Altitude | 50,000 | | | feet |
| Shock / Vibration(MIL-STD-810F) | 25g rms (15 degree 2KHz) endurance, 1 hour per axis | | | |
| Shock(non operating) | 20G for 11msc half sin wave,3 axis both directions | | | |


## Ordering Information:

| Base Number | Description | Revision |
|---|---|---|
| TC-80120-10S | Coaxial Directional Coupler<br>8-12GHz, Coulping:10dB, SMA Female | Rev.1.0 |

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

## Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.