泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Coax Directional Coupler

1-18GHz/10dB Coupling/N Female

Model: TC-10180-10N

TC-10180-10N is a coaxial directional coupler that delivers a 10 dB nominal coupling level and 12 dB minimum directivity across the full frequency range from 1 to 18 GHz. It is a three-port passive device that can couple a portion of the power from the main transmission line to the auxiliary line in a directional manner.

Features:

- Output Frequency: 1-18GHz
- Coupling: 10dB Typ
- Stackable mechanical design
- Low Insertion Loss
- Moderate Directivity
- 50 Ohm Matched Input / Output

Applications:

- Test Labs
- Instrumentations
- Sub-assemblies

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	1		18	GHz
Insertion Loss (Excl Coupling)		0.9	1.3	dB
Nominal Coupling Loss		0.46		dB
Coupling		10±1.5		dB
Directivity	12	15		dB
Power Handling			30	W
VSWR			1.5	:1
Impedance		50		Ohms


Mechanical Specifications:

Parameter	Value	Units
Input/Output Connector	N Female/N Female	
Size	83*20*20	mm

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Temperature Range	-45		+85	℃
Relative humidity	100% RH at 35c, 95%RH at 40℃			%
Altitude	50,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Base Number	Description	Revision
TC-10180-10N	Coaxial Directional Coupler 1-18GHz, Coulping:10dB, N Female	Rev.1.0