

Flexible Waveguide Cable

WR10/75-110GHz

Model: FW-WR10WR10-4m-A

FW-WR10WR10-4m-A is a flexible waveguide cable that covers the frequency range of 75 to 110 GHz. The flexible waveguide cable includes two WR-10 waveguide ports with UG-387/U-M anti-cocking flange.

Features:

- Operating Frequency 75 to 110GHz
- VSWR: 1.4:1 Typ
- Insertion loss: 50dB Typ
- Low cost
- Fast delivery time

Applications:

- Test Lab
- Instrumentations
- System setups

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency Range	75		110	GHz
VSWR		1.4		:1
Insertion Loss		50		dB
Power Handling		4 CW		W


Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	+25	°C
Non-operating Temperature	-55~+165	°C
Minimum Bending Radius	25	mm
Waveguide Connector	WR-10/UG-387/U	
Length*	4	m

*Note:Length can be customized.

Outline Drawing:

Unit:mm; Tolerance:±0.1mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:


Base Number	Description
FW-WR10WR10-4m-A	Flexible Waveguide Cable, 75-110GHz, WR10, Length can be customized

Typical Performance Data:

VSWR vs Frequency



Insertion Loss vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.