Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Waveguide Bandpass Filter

WR-08/100-112GHz

Model: TLBF-100112-45-08

TLBF-100112-45-08 is a waveguide bandpass filter with a passband frequency from 100 to 112 GHz and a rejection frequency from DC to 92 GHz and 122 to 140 GHz. The maximum insertion loss of the filter is 2 dB and the minimum rejection is 45 dBc. The input and output port configuration offers an inline structure with WR-08 waveguides and UG-387/U-M anti-cocking flanges.

Features:

- Passband Frequency Range 100 to 112 GHz
- Lower Cost
- Low Insertion Loss
- High Rejection

Applications:

- Communicatin Systems
- Radar Systems
- Sub-assemblies

Electrical Characteristics:

Parameter		Min	Typ	Max	Units
Passband Frequency range		100		112	GHz
Passband Width			12		GHz
Input/Output VSWR			1.3		:1
Passband Insertion Loss				2	dB
Rejection	@DC-92 GHz	45			dBc
	@122-140 GHz	45			


Envrionmental And Physical Characteristics:

Parameter	Description	Units
Operating Temerature	-20 to +55	℃
Storage Temerature	-20 to +55	℃
Material	Aluminum	
Finish	Conductive Coating, Natural Finish	
Waveguide	WR-08/UG-387/U-M	

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-100112-45-08	Waveguide Bandpass Filter,100-112GHz, Insertion Loss: 2dB, Rejection: 45dBc@DC-92GHz&122-140GHz,WR-08/UG-387/U-M	Rev.1.0