

## Power Amplifier

0.7-6GHz/30dB Gain/35dBm Psat

Model: TLPA0.7G6G-30-35

TLPA0.7G6G-30-35 is a power amplifier with a minimum gain of 30 dB and a nominal Psat of 35 dBm across the frequency range of 0.7 to 6 GHz. The DC power requirement for the amplifier is +28 VDC/1 A. The input and output port configuration offers coax adapter structure with SMA female.

### Features:

- Frequency range: 0.7-6GHz
- Gain: 30dB Min
- Output Power Psat: 35dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.7		6	GHz
增益 Gain	30	33		dB
增益平坦度 Gain Flatness		±2	±2.5	dB
线性输出功率 Output P1dB	33	34		dBm
饱和输出功率 Output Psat		35		dBm
杂散 Spurious		-60		dBc
输入驻波 Input VSWR		1.6	2.0	:1
直流电压 DC Voltage		+28		V DC
直流电流 DC Supply Current		1		A
阻抗 Impedance		50		Ohms

## 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	67*80*12	mm


## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+28 V
输入功率 RF Input Power	+10 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



## 外形图 Outline Drawing:

Unit:mm



**\*\*\*Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

\*Note: For a wider temperature range, please consult the manufacturer.

## 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.7G6G-30-35	Power amplifier 0.7-6GHz, Gain:30dB,Psat:35dBm,+28V DC,Without Heatsink	Rev.1.2
TLPA0.7G6G-30-35-HS	Power amplifier 0.7-6GHz, Gain:30dB,Psat:35dBm,+28V DC,With Heatsink	Rev.1.2