

Solid State High Power Amplifier Systems

1.1-1.4GHz/53dB Gain/53dBm Psat/220V AC

Model: TLPA1.1G1.4G-53-53-BC

TLPA1.1G1.4G-53-53-BC is a solid state high power amplifier systems provides high output power and high gain across the 1.1 to 1.4 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 1.1-1.4GHz
- Gain: 53dB Min
- Psat Output Power: 53dBm Min
- Protection: Over TEM, over voltage, over current ,infinite VSWR protection
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	1.1-1.4			GHz
功率增益 Power Gain	GP	53	54		dB
增益平坦度 Gain flatness	ΔGL		±1	±2	dB
线性输出功率 Output P1dB	P1dB		50		dBm
饱和输出功率 Output Psat	Psat	53			dBm
杂散 Spurious	Spur			-60	dBc
谐波 Harmonics	HAM			-10	dBc
输入驻波 Input VSWR	VSWRin		1.5	2	:1
交流电压 AC Voltage	Vac	110	220		V AC
交流电流 AC Supply Current	Iac		5		A
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	N Female/N Female	
正向/反向耦合 Forward/Reverse Coupling	SMA Female/ SMA Female	
尺寸 Size	3U*500	mm
重量 Weight	≤17	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,Infinite VSWR
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	°C
存储温度 Non-operating Temperature*	-30		+50	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLPA1.1G1.4G-53-53-BC	Solid State High Power Amplifier Systems 1.1-1.4GHz,Gain:53dB,Psat:53dBm,220V AC,Built in Fan Cooling	Rev.1.1

典型曲线 Typical Performance Data:


Small Signal Gain vs Frequency



Input VSWR vs Frequency




Gain vs Output Power




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


PndB vs Frequency



Psat vs Frequency




2nd Harmonic vs Output Power




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

3rd Harmonic vs Output Power



4th Harmonic vs Output Power



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.