

Power Amplifier

0.01-1GHz/30dB Gain/20dBm P1dB

Model: TLPA10M1G-30-20

TLPA10M1G-30-20 is a power amplifier with a typical small signal gain of 30 dB and a minimum Psat of 20 dBm across the frequency range of 0.01 to 1 GHz. The DC power requirement for the amplifier is +15 VDC/0.3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.01-1GHz
- Gain: 30dB Typ
- Output Power Psat: 21dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.01		1	GHz
小信号增益 Small Signal Gain	28	30		dB
增益平坦度 Gain Flatness		±0.8	±1	dB
噪声系数 Noise Figure		4		dB
线性输出功率 Output P1dB	20	21		dBm
饱和输出功率 Output Psat	21	22		dBm
输入驻波 Input VSWR		1.5	2.0	:1
输出驻波 Output VSWR		1.5	2.5	:1
直流电压 DC Voltage	12	15	16	V DC
静态电流 Quiescent Current		0.2		A
饱和电流 Saturation Current		0.25	0.3	A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	76*48*15	mm
重量 Weight	200	g

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+16 V
输入功率 RF Input Power	5dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA10M1G-30-20	Power amplifier 0.01-1GHz,Gain:30dB,Psat:20dBm, +15V DC,Without Heatsink	Rev.1.0
TLPA10M1G-30-20-HS	Power amplifier 0.01-1GHz,Gain:30dB,Psat:20dBm, +15V DC,With Heatsink	Rev.1.0