

J-Band,2-Way Waveguide Power Divider

220-330GHz/2.5dB,Insertion Loss/17dB,Isolation

Model: TLPD-220330-2-3.4

The TLPD-220330-2-3.4 is a full band WR-3.4, 2-way power divider that operates from 220 to 330 GHz. The power divider offers a typical insertion loss of 2.5dB and typical isolation of 17 dB. All ports are well-balanced and in-phase for power dividing or combining applications across the band. The power divider is configured as an inline package with WR-3.4 waveguides and UG-387/U-M compatible anti-cocking flanges at all ports .

Features:

- Frequency range: 220-330GHz
- Low Insertion Loss
- High Isolation
- Compact Package

Applications:

- Test Lab
- Sub-assemblies
- Test Instrumentations
- Twist Compatible

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	220		330	GHz
插损 Insertion Loss		2.5		dB
幅度平衡 Amplitude Balance		±1.2		dB
端口隔离 Port Isolation		17		dB
输入回波损耗 Input Return Loss		-15		dB
输出回波损耗 Output Return Loss		-15		dB

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	WR-3.4/UG-387/U	
尺寸 Size	20*25*40	mm
材质 Material	Brass	
表面处理 Finish	Gold plated	

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-45		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPD-220330-2-3.4	2-Way waveguide power divider, 220-330 GHz, Insertion loss: 2.5 dB, Port Isolation: 17dB	Rev.1.0