

Flexible Waveguide Cable

WR15/50-75GHz

Model: FW-1.0MWR15-0.1m

FW-1.0MWR15-0.1m is a flexible waveguide cable that covers the frequency range of 50 to 75 GHz. The flexible waveguide cable includes two WR-15 waveguide ports with UG-385/U-M anti-cocking flange.

Features:

- Operating Frequency 50 to 75GHz
- VSWR: 1.6:1 Typ
- Insertion loss: 2dB Typ
- Low cost
- Fast delivery time

Applications:

- Test Lab
- Instrumentations
- System setups

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency Range	50		75	GHz
驻波 VSWR		1.6		:1
插损 Insertion Loss		2		dB
耐功率 Power Handling		4 CW		W


环境和机械特性 Environmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	+25	°C
存储温度 Non-operating Temperature	-55~+165	°C
最小弯曲半径 Minimum Bending Radius	25	mm
波导接口 Waveguide Connector	WR-15/UG-385/U	
长度 Length*	0.1	m

*Note:Length can be customized.

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


订货信息 Ordering Information:

标准型号 Base Number	描述 Description
FW-1.0MWR15-0.1m	Flexible Waveguide Cable, 50-75GHz, WR15, Length can be customized


典型曲线 Typical Performance Data:

Length=0.1m:

VSWR vs Frequency



Insertion Loss vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.