

Low Noise Amplifier

WR-4.3/190-260GHz/7dB NF/17dB Gain**Model: TMLA-190260-1970-04**

TMLA-190260-1970-04 is a H-Band low noise amplifier with a typical small signal gain of 17 dB and a nominal noise figure of 7 dB across the frequency range of 190 to 260 GHz. The DC power requirement for the amplifier is +5 VDC /35 mA. The input and output port configuration offers an inline structure with WR-4.3 waveguides and UG-387/U-M anti-cocking flanges.

Features:

- Frequency range:190-260GHz
- Gain: 17dB Typ
- Noise Figure: 7dB Typ
- Unconditional stability

Applications:

- Passive Imaging
- 5G Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	190		260	GHz
小信号增益 Small Signal Gain		17		dB
噪声系数 Noise Figure		7		dB
输入驻波 Input VSWR		3.5		:1
输出驻波 Output VSWR		4		:1
直流电压 DC Voltage		5		V DC
直流供电 DC power supply		35		mA

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入接口 Input Connector	WR-4.3/ UG-387/U	
输出接口 Output Connector	WR-4.3/ UG-387/U	
供电引脚 Power Supply Pin	Solder Pin	
尺寸 Size	30*30*23	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+8 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-45		+85	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TMLA-190260-1970-04	Low Noise Amplifier,190-260GHz, Noise Figure:7.0dB, Gain:17dB,+5V DC,WR-4.3	Rev.1.0