泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

Power Amplifier

1-6GHz/53dB Gain/53dBm Psat

Model: TLPA1G6G-53-53-V2

TLPA1G6G-53-53-V2 is a power amplifier with a minimum small signal gain of 53 dB and a minimum Psat of 53 dBm across the frequency range of 1 to 6 GHz. The DC power requirement for the amplifier is +28 VDC/45 A. The input ports configuration offers coax adapter structure with SMA female and output ports configuration offers coax adapter structure with N female.

Features:

- Frequency range: 1-6GHz
- Gain: 53dB Min
- Output Power Psat: 53dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	1		6	GHz
小信号增益 Small Signal Gain	53	57		dB
增益平坦度 Gain Flatness		±4	±5	dB
线性输出功率 Output P1dB		47		dBm
饱和输出功率 Output Psat	53	53.5		dBm
输入驻波 Input VSWR		1.5	2	:1
直流电压 DC Voltage	26	28	30	V DC
静态电流 Static Current		3		A
饱和电流 Saturation current		45	50	A
阻抗 Impedance		50		Ohms

泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/N Female	
尺寸 Size	366*358*135.5	mm
重量 Weight	≤8	Kg

绝对最大值 Absolute Maximum Ratings:


参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+32 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Simple 220V System
Available SAC option

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

直流供电接口 DC Supply Connector(WS28-Z-8 Female):

引脚 Pin	名称 Name	功能 Function
1~4	VCC	电源正极,+26.0-30.0VDC
5~8	GND	地

控制接口 Control Connector(DSUB-9 Female):

引脚 Pin	名称 Name	功能 Function
1	EN	放大器使能：TTL高(5V)(内拉高) 放大器禁用：接地
2	NC	未连接
3	Over TEM	当外壳温度超过75℃时，功率放大器关闭，此引脚TTL电平拉高为5V。如果机箱温度降至70℃，功率放大器将恢复正常工作，此引脚TTL电平拉低为0V。
4	RESET	当应用和释放逻辑低电平时复位PA(内部Pulled-High)
5	GND	地
6~9	NC	未连接

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	℃
存储温度 Non-operating Temperature*	-30		+60	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA1G6G-53-53-V2	Power amplifier 1-6GHz, Gain:53dB,Psat:53dBm,+28V DC,With Heatsink	Rev.1.0