泰莱微波
Talent Microwave

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

F–Band VNA Frequency Extender

90-140GHz/WR-08

Model: TLVE-90140-N3-8

TLVE-90140-N3-8 frequency extenders are a dedicated Test & Measurement solution for extending the range of your Vector Network Analyzer (VNA) to 90-140 GHz.

Features:

- Frequency range: 90-140GHz
- Port Output Power (No Attenuation): -3dBm Typ
- Dynamic Range @10Hz BW: 100dB Minp
- Unconditional stability

Applications:

- VNA Frequency Extension
- Antenna measurements
- Material characterisation

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	90		140	GHz
测试端口输出功率 Test Port Output Power		-3		dBm
测试端口输入功率 Test Port Input Power (Damage)			20	dBm
输出功率衰减 Output Power Attenuation (Option:Variable attenuators)	0		30	dB
动态范围 Dynamic Range @10Hz BW	100			dB
方向性 Directivity		30		dB
射频输入频率 RF Input Frequency	11.25		17.5	GHz
射频输入功率 RF Input Power	3	5	7	dBm
RF倍频次数 RF Multiplication Factor		8		
本振输入频率 LO Input Frequency	11.25		17.5	GHz
本振输入功率 LO Input Power	3	5	7	dBm
LO倍频次数 LO Multiplication Factor		8		
中频频率范围 IF Frequency Range	1		1000	MHz
幅度稳定度 Amplitude stability@300 Hz BW		±0.15		dB
相位稳定度 Phase Stability@300Hz BW		±1.5		°

Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value
RF/LO输入接口 RF/LO Input Connector	SMA Female
MEA/REF IF输出接口 MEA/REF IF Output Connector	SMA Female
测试端口 Test Port Connector	WR-08/UG-387/U
供电 Power Supply Pin	FGG 0B 4 Core
尺寸 Size	210*81*46.2mm

绝对最大值 Absolute Maximum Ratings :

参数 Parameter	指标 Value	单位 Units
测试端输入功率 Test Port Input Power	+20	dBm
RF/LO端损坏等级 RF/LO Port Damage Level	+10	dBm
供电偏置 Supply Bias Voltage	+240 V AC	
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V	


环境和物理特性 Envrionmental And Physical Characteristics:

参数 Parameter	指标 Value	单位 Units
操作温度 Operating Temerature	0 to +45	℃
存储温度 Storage Temerature	-55 to +125	℃
材质 Material	Aluminum	
表面处理 Finish	Gray spray paint	


Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm




TLVE-90140-N3-8-A



TLVE-90140-N3-8

原理框图 Block Diagrams:



Suzhou Talent Microwave,Inc
sales@talentmw.com
www.talentmw.com

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号 Revision
TLVE-90140-N3-8	F-band VNA Frequency Extender, 90-140 GHz, Output Power: -3dBm typ; Dynamic Range: 100dB Min; Magnitude Stability @300Hz BW: ±0.15dB, Phase Stability @300Hz BW: ±1.5°	Rev.1.0
TLVE-90140-N3-8-A	F-band VNA Frequency Extender, 90-140 GHz, Output Power: -3dBm typ; Dynamic Range: 100dB Min; Magnitude Stability @300Hz BW: ±0.15dB, Phase Stability @300Hz BW: ±1.5°,with Micrometer driven variable attenuators	Rev.1.0

随货配件 Components Included:

标准型号 Part Number	描述 Description	数量 Quantity
S1-SMAMSMAM-1.2m	COAXIAL CABLE ASSEMBLY	4 PCS
TLACTDC-22012	AC-to-DC Power Adapter	1 PCS

Notes:

1. Dimensions and specifications may be changed without prior notice.
2. Standard Warranty:three years.