



Electrical & Environmental Characteristics

Impedance	50 Ohm
Insulation Resistance	10000 MΩ
Operating Frequency	50GHz
Dielectric Withstanding Voltage	1000 V
VSWR	1.20:1

Insertion Loss	0.05* $\sqrt{f_{GHz}}$ dB
Operating Temperature	-40~+165℃

Material & Coat-Plating

Inner Conductor	Beryllium copper, Gold
Dielectric	PEI
Body	Stainless Steel, Passivated
Coupling Nut	Stainless Steel, Passivated

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc				
		CHK					
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Mode NMD2.4/2.4-JYJG NMD2.4mm Male to 2.4mm Male Adaptor				
		PRODUCT SPEC					
		APPLICATION SPEC					
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO		
		CUSTOMER DRAWING		SCALE 4: 1	SCALE 4: 1	SHEET1 OF 1	RVE 1