

**Model:TMAM-050075-0615-15**
**V-Band Active Multiplier  
 x6, 50-75 GHz, +14 dBm Output Power,**
**Feature:**

- Output Frequency: 50-75GHz
- Output Power : 14dBm Typ
- Low power consumption

**电气特性 Electrical:**

参数Parameter	Min.	Typ.	Max.	单位Units
输出频率 Output Frequency	50		75	GHz
输出功率 Output Power		14		dBm
输入频率 Input Frequency	8.33		12.5	GHz
输入功率 Input Power	4	5	6	dBm
倍频次数 Multiply Factor		6		
输入驻波 Input VSWR		10		:1
输出驻波 Output VSWR		10		:1
供电电压 DC Voltage		5.5		V
供电电流DC Supply Current		250		mA

**机械特性 Mechanical :**

参数Parameter	指标 Value	单位Units
输出接口Output Connector	WR-15/UG-385/U	
输入接口Input Connector	SMA Female	
直流偏置 Bias	Solder Pin	
尺寸 Size	42×24×30	mm



 Available 220V System  
 Benchtop Amplifier

**绝对最大值 Absolute Maximum Ratings:**

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+5.5V
输入功率 RF INPUT POWER	6 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

**外形尺寸 Outline Drawing:**

Unit: mm(Inches)



OBSERVE PRECAUTIONS  
ELECTROSTATIC SENSITIVE  
DEVICES

**温度环境 Environmental Conditions:**

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-25		+75	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

**订货信息 Ordering Information:**

标准型号 Part Number	描述 Description	版本号Revision
TMAM-050075-0615-15	V-Band Active Multiplier X6, 50-75 GHz, +14 dBm Output Power, WR-15	Rev.1.1