

Model:TMAM-071086-0213-12
**W-Band Active Multiplier
 X2, 71-86 GHz ,+13 dBm Output Power,**
Feature:

- Output Frequency: 71-86GHz
- Output Power : 13dBm Typ
- Low power consumption

电气特性 Electrical:

参数Parameter	Min.	Typ.	Max.	单位Units
输出频率 Output Frequency	71		86	GHz
输出功率 Output Power	10	13	16	dBm
输入频率 Input Frequency	35.5		43	GHz
输入功率 Input Power	-2	0	+2	dBm
倍频次数 Multiply Factor		2		dB
输入驻波 Input VSWR		2.0		:1
输出驻波 Output VSWR		3.0		:1
供电电压 DC Voltage		5.5		V
供电电流DC Supply Current		310		mA

机械特性 Mechanical :

参数Parameter	指标 Value	单位Units
输出接口Output Connector	WR-12/UG-387	
输入接口Input Connector	SMA Female	
直流偏置 Bias	Solder Pin	
尺寸 Size	48×30×24	mm



 Available 220V System
 Benchtop Amplifier

绝对最大值 Absolute Maximum Ratings:

参数Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	5.5V
输入功率 RF INPUT POWER	2dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形尺寸 Outline Drawing:

Unit: Inches(mm)



OBSERVE PRECAUTIONS
ELECTROSTATIC SENSITIVE
DEVICES

温度环境 Environmental Conditions:

参数Parameter	Min.	Typ.	Max.	单位Units
操作温度 Operating Temperature	-10		+55	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Part Number	描述 Description	版本号Revision
TMAM-071086-0213-12	W-Band Active Multiplier X2, 71-86 GHz ,+13 dBm Output Power,WR-12	Rev.1.1