

Power Amplifier

WR-03/215-225GHz /15dB Gain/15 dBm Psat**Model: TMPA-215225-1515-03**

TMPA-215225-1515-03 is a power amplifier with a typical small signal gain of 15 dB and Psat of 15 dBm across the frequency range of 215 to 225 GHz. The DC power requirement for the amplifier is +12 VDC/320 mA. The input and output port configuration offers an inline structure with WR-03 waveguides and UG-387/U-M antcocking flanges.

Features:

- Frequency range: 215-225 GHz
- Gain: 15dB Typ
- Output Power Psat: 15dBm Min
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	215-225			GHz
Small Signal Gain		15		dB
Output Psat	15			dBm
Input VSWR			2	:1
Output VSWR		2.5		:1
DC Voltage		12		V DC
DC Supply Current		320		mA

Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	WR-03/UG-387/U	
DC Bias	Solder Pin	
Size	40*40*23(Without Heatsink)	mm

Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+15 V
RF Input Power	+13 dBm
ESD sensitivity (HBm)	Class 0, passed 150V

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.


Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature	-10		+65	°C
Non-operating Temperature	-45		+85	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:

Base Number	Description	Revision
TMPA-215225-1515-03	Power Amplifier, 215-225GHz, Gain:15 dB Type, P _{sat} :15 dBm Min, +12V DC,WR-03	Rev.1.1


Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:

VSWR vs Frequency



Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.