

## E-Band Power Amplifier

**WR-12/60-90GHz /34dB Gain/20 dBm Psat****Model: TMPA-060090-3520-12**

TMPA-060090-3520-12 is a E-Band power amplifier with a typical small signal gain of 34 dB and a nominal Psat of 20 dBm across the frequency range of 60 to 90 GHz. The DC power requirement for the amplifier is +12 VDC/330 mA. The input and output port configuration offers an inline structure with WR-12 waveguides and UG-387/U-M antickocking flanges.

### Features:

- Ultra Wide Band: 60-90GHz
- Gain: 34dB Typ
- Output Power Psat: 20dBm Typ
- Good Power and Gain Flatness

### Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

### Electrical Characteristics:

| Parameter         | Min   | Typ | Max | Units |
|-------------------|-------|-----|-----|-------|
| Frequency range   | 60-90 |     |     | GHz   |
| Small Signal Gain |       | 34  |     | dB    |
| Output Psat       |       | 20  |     | dBm   |
| Input VSWR        |       | 2   |     | :1    |
| Output VSWR       |       | 2   |     | :1    |
| DC Voltage        |       | 12  |     | V DC  |
| DC Supply Current |       | 330 |     | mA    |

### Mechanical Specifications:


| Parameter               | Value          | Units |
|-------------------------|----------------|-------|
| Input /Output Connector | WR-12/UG-387/U |       |
| DC Bias                 | Solder Pin     |       |
| Size                    | 45*30*20       | mm    |
| Weight                  | /              | g     |

## Absolute Maximum Ratings:

| Parameter             | Value                |
|-----------------------|----------------------|
| Supply Bias Voltage   | +15 V                |
| RF Input Power        | +15 dBm              |
| ESD sensitivity (HBm) | Class 0, passed 150V |

## Outline Drawing:

Unit:mm




### Environmental Conditions:

| Parameter                       | Min                                                 | Typ | Max | Units |
|---------------------------------|-----------------------------------------------------|-----|-----|-------|
| Operating Temperature           | -10                                                 |     | +65 | °C    |
| Non-operating Temperature       | -45                                                 |     | +85 | °C    |
| Relative humidity               |                                                     | 95  |     | %     |
| Altitude                        | 10,000                                              |     |     | feet  |
| Shock / Vibration(MIL-STD-810F) | 25g rms (15 degree 2KHz) endurance, 1 hour per axis |     |     |       |
| Shock(non operating)            | 20G for 11msc half sin wave,3 axis both directions  |     |     |       |

### Ordering Information:

| Base Number         | Description                                                                                  | Revision |
|---------------------|----------------------------------------------------------------------------------------------|----------|
| TMPA-060090-3520-12 | Power Amplifier, 60-90 GHz, Gain:34 dB Type,<br>P <sub>sat</sub> :20 dBm Type, +12V DC,WR-12 | Rev.1.1  |


### Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

## Typical Performance Data:

### VSWR vs Frequency



### Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.