

Absorptive, Broadband PIN Switch

0.5-54GHz/SPDT/ 1.85mm Female

Model: TLSPDT0.5G54GA

The TLSPDT0.5G54GA is an absorptive PIN diode based switch with a TTL driver that operates between 0.5 and 54 GHz. The SPDT switch offers 70 dB port-to-port isolation with a typical switching speed of 100 ns. The input and output connectors of the switch are 1.85 mm female.

Features:

- Frequency range: 0.5-54GHz
- Low Insertion Loss: 8.0 dB
- Power Handling : 20 dBm
- High Isolation
- Switch Type: Absorptive

Applications:

- Communication Systems
- Automatic Test Equipment
- Switching Network

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.5-54			GHz
插损 Insertion Loss		8	8.5	dB
隔离 Isolation	70			dB
切换速度 Switch Speed			100	ns
输入驻波 Input VSWR		2	2.5	:1
输出驻波 Output VSWR		2	2.5	:1
耐功率 Power Handling			20	dBm
直流电压 DC Supply Voltage		+/-5		V DC
控制电平 Control Logic TTL		0/+5		V DC
直流电流 DC Supply Current		150/-80		mA
开关类型 Switch type	Absorptive			
阻抗 Impedance	50			Ohms

绝对最大值 Absolute Maximum Ratings :


描述 Description	参数 Parameter	单位 Units
供电偏置电压 Supply Bias Voltage	±5%	V
射频输入功率 RF Input Power	20	dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V	

机械特性 Mechanical Specifications:

描述 Description	参数 Parameter	单位 Units
输入/输出接口 Input /Output Connector	1.85mm Female/1.85mm Female	
直流控制接口 Control Bias	Solder Pin	
尺寸 Size	60*20*12	mm

外形图 Outline Drawing:

Unit:mm



真值表 Truth Table

TTL Control Input	Signal Path State
C1	
0	J0-J1
1	J0-J2

TTL Control Voltages &VDD

Stage	Bias Condition
VDD	+5V (±5%)
VEE	-5V (±5%)
Low (0)	0 to 0.8Vdc
High (1)	2.0 to +5.0Vdc



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-25		+85	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLSPDT0.5G54GA	Absorptive,Broadband PIN Switch 0.5-54 GHz,SPDT,1.85mm	Rev.1.1