

Solid State High Power Amplifier Systems

2.5-7.5GHz/57dB Gain/57dBm Psat/380V AC

Model: TLPA2.5G7.5G-57-57-BC

TLPA2.5G7.5G-57-57-BC is a solid state high power amplifier systems provides high output power and high gain across the 2.5 to 7.5 GHz frequency range. The amplifier features a built-in 380V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 2.5-7.5GHz
- Gain: 57dB Min
- Psat Output Power: 57dBm Min
- Protection:Over TEM,over voltage, over current ,over VSWR protection
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	2.5-7.5			GHz
功率增益 Power Gain	GP	57			dB
增益平坦度 Gain flatness	ΔGL		±4		dB
饱和输出功率 Output Psat	Psat	57			dBm
杂散 Spurious@Pout=57dBm	Spur		-60	-50	dBc
谐波 Harmonics	HAM		-15	-10	dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac		380		V AC
功耗 Power Consumption	Pdiss			5000	W
阻抗 Impedance	I/O-IMP	50			Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	N Female/L29 Female or WRD250	
尺寸 Size	12U	
重量 Weight	≤150	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off 2,ALC automatic level control 3,RF setting On/Off
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,Over VSWR
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system,forced air cooling

温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	℃
存储温度 Non-operating Temperature*	-30		+50	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Desciption	版本号 Revision
TLPA2.5G7.5G-57-57-BC	Solid State High Power Amplifier Systems 2.5-7.5GHz,Gain:57dB,Psat:57 dBm,380V AC,Built in Fan Cooling	Rev.1.1


典型曲线 Typical Performance Data:




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Input VSWR vs Frequency



P1dB vs Frequency




Pout@Pin




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Pout@Equal_Pin



Spurious vs Frequency



Harmonic vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.