

Solid State High Power Amplifier Systems

18-40GHz/50dB Gain/50dBm Psat/380V AC

Model: TLPA18G40G-50-50-BC

TLPA18G40G-50-50-BC is a solid state high power amplifier systems provides high output power and high gain across the 18 to 40 GHz frequency range. The amplifier features a built-in 380V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 18-40GHz
- Gain: 50dB Min
- Psat Output Power: 50dBm Typ
- Protection: Over TEM, over voltage, over current, infinite VSWR protection
- 50 Ohm Matched Input / Output



Electrical Characteristics:

Parameter	Symbol	Min	Typ	Max	Units
Frequency range	BW	18-40			GHz
Power Gain	GP	50			dB
Gain flatness	ΔGL		± 5		dB
Output Psat	Psat		50		dBm
Spurious@Pout=50dBm	Spur			-50	dBc
Harmonics@Pout=50dBm	HAM			-15	dBc
Input VSWR	VSWRin			2.0	:1
AC Voltage	Vac		220		V AC
Power Consumption	Pdiss			3500	W
Impedance	I/O-IMP	50			Ohms

Mechanical Specifications:


Parameter	Value	Units
Input /Output Connector	2.92mm Female/WRD180	
Communication Connector	DB9/RJ45	
Size	19 Inch 6U	
Weight	≤ 55	Kg

Absolute Maximum Ratings:

Parameter	Value
RF Input Power	+5 dBm
ESD sensitivity (HBM)	Class 0, passed 150V

Outline Drawing:

Unit:mm



Key Features:

Parameter	Advantages
Control functions	1, ProgrAm_controlled switching machine by network port&RS422 2,Adjust output power
Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,infinite VSWR
Display functions	1,Display the current out/reflected power 2,Display fault information
Cooling system	Built in Cooling system,forced air cooling

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-20		+40	°C
Non-operating Temperature*	+30		+50	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA18G40G-50-50-BC	Solid State High Power Amplifier Systems 18-40GHz, Gain:50dB, Psat:50dBm, 380V AC, Built in Fan Cooling	Rev.1.1