

## Solid State High Power Amplifier Systems

27-32GHz/53dB Gain/53dBm Psat/220V AC

Model: TLPA27G32G-53-53-BC

TLPA27G32G-53-53-BC is a solid state high power amplifier systems provides high output power and high gain across the 27 to 32 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

### Features:

- Frequency range: 27-32GHz
- Gain: 53dB Min
- Psat Output Power: 53dBm Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output



### 电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	27-32			GHz
功率增益 Power Gain	GP	53			dB
增益平坦度 Gain flatness	$\Delta$ GL		$\pm 4$		dB
饱和输出功率 Output Psat	Psat	53			dBm
杂散 Spurious	Spur			-55	dBc
输入驻波 Input VSWR	VSWRin			2.0	:1
交流电压 AC Voltage	Vac		220		V AC
功耗 Power Consumption	Pdiss			3000	W
阻抗 Impedance	I/O-IMP	50			Ohms


### 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.92mm Female/WR28	
正向/反向耦合 Forward/Reverse Coupling	2.92mm Female/2.92mm Female	
尺寸 Size	19 Inch 5U	
重量 Weight	$\leq 45$	Kg

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

## 外形图 Outline Drawing: Unit:mm



## 主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	Power setting on/off
显示功能 Display functions	1,Current 2,Output/reflected power 3,Fault informations
内置保护功能 Protection functions	1,Over TEM 2,Over voltage 3,Over current 4,Over VSWR
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system,forced air cooling

## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	°C
存储温度 Non-operating Temperature*	-30		+50	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


\*Note: For a wider temperature range, please consult the manufacturer.

## 订货信息 Ordering Information:


标准型号 Base Number	描述 Description	版本号 Revision
TLPA27G32G-53-53-BC	Solid State High Power Amplifier Systems 27-32GHz,Gain:53dB,Psat:53dBm,220V AC,Built in Fan Cooling	Rev.1.1

**典型曲线 Typical Performance Data:**


**Small Signal Gain vs Frequency**



**Input VSWR vs Frequency**






**PndB vs Frequency**



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

**典型曲线 Typical Performance Data:**



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.