

Low Noise Amplifier

0.5-8GHz/1.4dB NF/21dB Gain/16dBm P1dB

Model: TLLA0.5G8G-21-14

TLLA0.5G8G-21-14 is a low noise amplifier with a typical small signal gain of 21 dB and a nominal noise figure of 1.4 dB across the frequency range of 0.5 to 8 GHz. The DC power requirement for the amplifier is +12 V DC/50 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.5-8GHz
- Gain: 21dB Typ
- Noise Figure: 1.4dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	0.5		8	GHz
Small Signal Gain		21		dB
Gain Flatness		±2.0		dB
Noise Figure		1.4		dB
Output P1dB		16		dBm
Output IP3		30		dBm
Input VSWR		2.5		:1
Output VSWR		2		:1
DC Voltage	+8	+12	+15	V DC
DC Supply Current		50		mA
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	SMA Female/SMA Female	
DC Bias	Solder Pin	
Size	28*20*10	mm
Weight	55	g



Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+15 V
RF Input Power	+10 dBm
ESD sensitivity (HBm)	Class 0, passed 150V



Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**

Environmental Conditions:


Parameter	Min	Typ	Max	Units
Operating Temperature	-45		+85	°C
Non-operating Temperature	-55		+125	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

Ordering Information:


Base Number	Description	Revision
TLLA0.5G8G-21-14	Low Noise Amplifier, 0.5-8GHz, Noise Figure:1.4dB, Gain: 21dB,P1dB:16dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA0.5G8G-21-14-HS	Low Noise Amplifier, 0.5-8GHz, Noise Figure:1.4dB, Gain: 21dB,P1dB:16dBm,+12V DC,With Heatsink	Rev.1.1

Typical Performance Data:

Gain&VSWR vs Frequency




Noise Figure vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency



P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.