

Solid State High Power Amplifier Systems

40-67GHz/40dB Gain/37dBm Psat/220V AC

Model: TLPA40G67G-40-37-BC

TLPA40G67G-40-37-BC is a solid state high power amplifier systems provides high output power and high gain across the 40 to 67 GHz frequency range. The amplifier features a built-in 220V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Wide Band: 40-67GHz
- Gain: 40dB Min
- Psat Output Power: 37dBm Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output



电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	40-67			GHz
功率增益 Power Gain	GP	40			dB
增益调节范围 Gain adjust Range	Δ GR		20		dB
增益调节步进 Gain adjust Step	Δ GS		0.5		dB
饱和输出功率 Output Psat	Psat	37			dBm
杂散 Spurious	Spur			-50	dBc
输入驻波 Input VSWR	VSWRin			2	:1
交流电压 AC Voltage	Vac		220		V AC
功耗 Power Consumption	Pdiss			200	W
阻抗 Impedance	I/O-IMP	50			Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	1.85mm Female/WR19	
正向/反向耦合 Forward/Reverse Coupling	1.85mm Female/1.85mm Female	
通信接口 Communication Connector	DB9/RJ45	
尺寸 Size	19 Inch 3U*550	mm
重量 Weight	\leq 30	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting On/Off 2, Output power control
显示功能 Display functions	1, Output/reflected power 2, Fault informations
内置保护功能 Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Over VSWR
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system, forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+50	°C
存储温度 Non-operating Temperature*	-30		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave, 3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA40G67G-40-37-BC	Solid State High Power Amplifier Systems 40-67GHz, Gain:40dB, Psat:37 dBm, 220V AC, Built in Fan Cooling	Rev.1.1