

Power Amplifier

0.1-4GHz/45dB Gain/41dBm Psat

Model: TLPA0.1G4G-45-41

TLPA0.1G4G-45-41 is a power amplifier with a typical small signal gain of 45 dB and a nominal Psat of 41 dBm across the frequency range of 0.1 to 4 GHz. The DC power requirement for the amplifier is +28VDC/2.5A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 0.1-4GHz
- Gain: 45dB Typ
- Output Power Psat: 41dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	0.1		4	GHz
小信号增益 Small Signal Gain		45		dB
增益平坦度 Gain Flatness		±3		dB
线性输出功率 Output P1dB	@0.1-1GHz	38		dBm
	@1-4GHz	40		
饱和输出功率 Output Psat		41		dBm
输入驻波 Input VSWR			1.8	:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current		2.5		A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	140*80*12	mm
重量 Weight	260	g


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+28 V
输入功率 RF Input Power	0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA0.1G4G-45-41	Power amplifier 0.1-4GHz, Gain:45dB,Psat:41dBm,+28V DC,Without Heatsink	Rev.1.1
TLPA0.1G4G-45-41-HS	Power amplifier 0.1-4GHz, Gain:45dB,Psat:41dBm,+28V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Power Gain vs Frequency



Gain vs Output Power




PndB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


P_{sat} vs Frequency



2nd Harmonics vs Output Power




3rd Harmonics vs Output Power



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.