



Electrical & Environmental Characteristics

Impedance	50 Ω
Insulation Resistance	5000 MΩ
Operating Frequency	DC~67GHz
Dielectric Withstanding Voltage	1000V
VSWR	≤1.15
Insertion Loss	≤0.05* $\sqrt{f_GHz}$
Operating Temperature	- 55~+165°C

Material & Coat-Plating

Inner Conductor	Beryllium Copper, Gold
Dielectric	PEI 1000
Body	Stainless Steel, Passivated
Coupling Nut	N/A

No.	Model	Pin Size Ød
1	1.85-KFD80709	0.23 [0.009]
2	1.85-KFD80712	0.30 [0.012]

THIS DRAWING IS A CONTROLLED DOCUMENT		DWN	Suzhou Talent Microwave, Inc			
		CHK				
Unit mm	TOLERANCES UNLESS OTHERWISE SPECIFIED 0 PLC ±0.25 1 PLC ±0.15 2 PLC ±0.12 3 PLC ± 3 PLC ± ANGLES ±1°	APVD	Product Model 1.85-KFD80709 1.85mm Female Flange Connector			
		PRODUCT SPEC				
		APPLICATION SPEC				
MATERIAL SEE TABLE	FINISH SEE TABLE	WEIGHT	SIZE A4	GAGE CODE 0T8L4	DRAWING NO	
		CUSTOMER DRAWING			SHEET 1 OF 1	RVE 1