

## Power Amplifier

60MHz-0.3GHz/30dB Gain/37dBm Psat

Model: TLPA60M0.3G-30-36

TLPA60M0.3G-30-36 is a power amplifier with a minimum gain of 30 dB and a minimum Psat of 37 dBm across the frequency range of 60MHz to 0.3 GHz. The DC power requirement for the amplifier is +28 VDC/0.5 A. The input and output port configuration offers coax adapter structure with SMA female.

### Features:

- Frequency range: 60MHz-0.3GHz
- Gain: 30dB Min
- Output Power Psat: 37dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

### Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

### 电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	60MHz		0.3GHz	
增益 Gain	30			dB
增益平坦度 Gain Flatness		±1	±2	dB
线性输出功率 Output P1dB	36			dBm
饱和输出功率 Output Psat	37			dBm
输入驻波 Input VSWR			2	:1
直流电压 DC Voltage		+28		V DC
直流电流 DC Supply Current		0.5		A
阻抗 Impedance		50		Ohms

## 机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	140*65*23	mm

## 绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+28 V
输入功率 RF Input Power	+12 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



## 外形图 Outline Drawing:

Unit:mm



**\*\*\*Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

## 温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+60	°C
存储温度 Non-operating Temperature*	-50		+70	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


\*Note: For a wider temperature range, please consult the manufacturer.

## 订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA60M0.3G-30-36	Power amplifier 60MHz-0.3GHz, Gain:30dB,Psat:37dBm,+28V DC,Without Heatsink	Rev.1.1
TLPA60M0.3G-30-36-HS	Power amplifier 60MHz-0.3GHz, Gain:30dB,Psat:37dBm,+28V DC,With Heatsink	Rev.1.1

## 典型曲线 Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

## 典型曲线 Typical Performance Data:


### Small Signal Gain vs Frequency



### Gain vs Output Power




### PndB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

**典型曲线 Typical Performance Data:**


**Psat vs Frequency**



**2nd Harmonics vs Output Power**




**3rd Harmonics vs Output Power**



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.