

Power Amplifier

2700-3200MHz/30dB Gain/44dBm Psat

Model: TLPA2700M3200M-30-44

TLPA2700M3200M-30-44 is a power amplifier with a minimum small signal gain of 30 dB and a minimum Psat of 44 dBm across the frequency range of 2700 to 3200MHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 2700-3200MHz
- Gain: 30dB Min
- Output Power Psat: 44dBm Min
- Good Power and Gain Flatness
- 44 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	2700		3200	MHz
小信号增益 Small Signal Gain	30	33		dB
增益平坦度 Gain Flatness		±1	±1.5	dB
饱和输出功率 Output Psat	44	45		dBm
输入驻波 Input VSWR		1.3	1.5	:1
输出驻波 Output VSWR			2	:1
直流电压 DC Voltage		+28	+30	V DC
直流电流 DC Supply Current		3	4.2	A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流供电接口 DC Power Supply Connector	J30J-9ZKP	
尺寸 Size	170*94*20	mm
重量 Weight	300	g


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+30 V
输入功率 RF Input Power	+20 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	20g,11ms,saw-tooth			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA2700M3200M-30-44	Power amplifier 2700-3200MHz, Gain:30dB,Psat:44dBm,+28V DC,Without Heatsink	Rev.1.1
TLPA2700M3200M-30-44-HS	Power amplifier 2700-3200MHz, Gain:30dB,Psat:44dBm,+28V DC,With Heatsink	Rev.1.1

典型曲线 Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Small Signal Gain vs Frequency



Small Signal Gain vs Output Power




PndB vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Psat vs Frequency



2nd Harmonics vs Output Power




3rd Harmonics vs Output Power



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.