

Solid State High Power Amplifier Systems

8-10GHz/57dB Gain/57dBm Psat/380V AC

Model: TLPA8G10G-57-57-BC

TLPA8G10G-57-57-BC is a solid state high power amplifier systems provides high output power and high gain across the 8 to 10 GHz frequency range. The amplifier features a built-in 380V power supply, making it easy to use in most lab environments. This model features thermal self protection, preventing damage to the amplifier and providing added reliability.

Features:

- Frequency range: 8-10GHz
- Gain: 57dB Min
- Psat Output Power: 57dBm Min
- Protection: Over TEM, over voltage, over current, over VSWR protection
- 50 Ohm Matched Input / Output

电气特性 Electrical Characteristics:

参数 Parameter	代码 Symbol	Min	Typ	Max	单位 Units
频率范围 Frequency range	BW	8		10	GHz
工作模式 Working Mode	MOD	CW/PULSE compatible			
功率增益 Power Gain	GP	57			dB
增益平坦度 Gain flatness	Δ GL		± 3		dB
增益调节范围 Gain adjust Range	Δ GR		20		dB
增益调节步进 Gain adjust Step	Δ GS		0.5		dB
饱和输出功率 Output Psat	Psat	57			dBm
杂散 Spurious@Pout=57dBm	Spur			-60	dBc
谐波 Harmonics@Pout=57dBm	HAM			-20	dBc
输入驻波 Input VSWR	VSWRin			1.5	:1
交流电压 AC Voltage	Vac		380		V AC
功耗 Power Consumption	Pdiss		5000		W
阻抗 Impedance	I/O-IMP		50		Ohms

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	N Female WR90	
正向/反向耦合 Forward/Reverse Coupling	N Female/N Female	
通信接口 Communication Connector	DB9/RJ45	
液晶显示屏 Front Panel LCD Screen Display	7 inch LCD Screen Display	
尺寸 Size	19 Inch 11U*800	mm
重量 Weight	≤250	Kg

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



主要功能 Key Features:

参数 Parameter	特点 Advantages
控制功能 Control functions	1, Power setting on/off 2, RF setting on/off 3, ALC automatic level control
内置保护功能 Protection functions	1, Over TEM 2, Over voltage 3, Over current 4, Over VSWR
监测功能 Monitoring function	1, Temperature 2, Working voltage/current 3, Output power
监控和控制 Remote control	RS422/Ethernet
冷却系统 Cooling system	Built in Cooling system, forced air cooling

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-20		+40	°C
存储温度 Non-operating Temperature*	-30		+50	°C
相对湿度 Relative humidity		95		%
海拔 Altitude		10,000		feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave, 3 axis both directions			

*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA8G10G-57-57-BC	Solid State High Power Amplifier Systems 8-10GHz, Gain:57dB, Psat:7dBm, 380V AC, Built in Fan Cooling	Rev.1.0