

Power Amplifier

8-12GHz/40dB Gain/40dBm Psat

Model: TLPA8G12G-40-40

TLPA8G12G-40-40 is a power amplifier with minimum small signal gain of 40 dB and a minimum Psat of 40 dBm across the frequency range of 8 to 12 GHz. The DC power requirement for the amplifier is +28 VDC/3 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 8-12GHz
- Gain: 40dB Min
- Output Power Psat: 40dBm Min
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	8		12	GHz
小信号增益 Small Signal Gain	40	42		dB
增益平坦度 Gain Flatness		±2		dB
线性输出功率 Output P1dB		38		dBm
饱和输出功率 Output Psat	40	41		dBm
谐波抑制 Harmonic		-15		dBc
输入驻波 Input VSWR		1.5	2	:1
直流电压 DC Voltage		28		V DC
直流电流 DC Supply Current		3		A
阻抗 Impedance		50		Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	60*60*11.5(Without heatsink) 150*127*74.5(With heatsink)	mm
重量 Weight	≤200	g

绝对最大值 Absolute Maximum Ratings:




参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+29 V
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



Simple 220V System
Available SAC option

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature*	-40		+50	°C
存储温度 Non-operating Temperature*	-50		+60	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLPA8G12G-40-40	Power amplifier 8-12GHz, Gain:40dB,Psat:40dBm,+28V DC,With Heatsink	Rev.1.2

典型曲线 Typical Performance Data:


VSWR&Gain vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:


Gain vs Output Power



P1dB vs Frequency




P3dB vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.