

Power Amplifier

WR-3.4/300-317GHz/9dB Gain/9dBm Psat

Model: TMPA-300317-0909-3.4

TMPA-300317-0909-3.4 is a power amplifier with a typical small signal gain of 9 dB and a nominal Psat of 9 dBm across the frequency range of 300 to 317 GHz. The DC power requirement for the amplifier is +12 VDC/215 mA. The input and output port configuration offers an inline structure with WR-3.4 waveguides and UG-387/U-M antickocking flanges.

Features:

- Frequency range: 300-317GHz
- Gain: 9dB Typ
- Output Power Psat: 9dBm Typ
- Good Power and Gain Flatness

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	300		317	GHz
小信号增益 Small Signal Gain		9		dB
饱和输出功率 Output Psat		9		dBm
输入驻波 Input VSWR		3		:1
直流电压 DC Voltage		12		V DC
直流电流 DC Supply Current		215		mA

机械特性 Mechanical Specifications:


参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	WR-3.4/UG-387/U	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	35.2*30*23(Without heatsink) 35.2*70*43(With heatsink)	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	TBD
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



温度环境 Environmental Conditions:


参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	℃
存储温度 Non-operating Temperature	-45		+85	℃
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TMPA-300317-0909-3.4	Power Amplifier, 300-317GHz, Gain: 9dB Type, Psat: 9dBm Type, +12V DC,WR-3.4, With heasink	Rev.1.0

典型曲线 Typical Performance Data:


Gain vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

典型曲线 Typical Performance Data:

Input VSWR vs Frequency



Psat vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.