

Coaxial Low-pass Filter

DC-1 GHz/SMA Female

Model: TLLF-DC-1G-L5

TLLF-DC-1G-L5 is a coaxial low-pass filter with a passband frequency from DC to 1 GHz and a rejection frequency from DC-2 GHz to 4 GHz. The maximum insertion loss of the filter is 0.8 dB and the minimum rejection is 40 dB.

Features:

- Passband Frequency Range DC to 1GHz
- Low Insertion Loss

Applications:

- Instrumentations
- Test Labs
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	DC		1	GHz
Passband Insertion Loss			0.8	dB
Pass band Ripple			0.6	dB
Rejection	>40dB@dc-2000-4000Mhz			
Power Handling			30	W
VSWR			1.6	:1
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	SMA Female	
Size	60*20*20	mm

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLLF-DC-1G-L5	Coaxial Low-pass Filter, Passband frequency range: DC-1GHz, Passband Insertion Loss: 0.8dB, SMA Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.