

Coaxial Band-pass Filter

2.375-2.625GHz/ SMA Female

Model: TLBF-2G5-5-E

TLBF-2G5-5-E is a coaxial band-pass filter with a passband frequency from 2.375 to 2.625GHz and a rejection frequencies from 0 to 1.75GHz and at 3.5GHz. The nominal insertion loss of the filter is 1.0dB and the typical rejection is 40 dB.

Features:

- Passband Frequency Range 2.375 to 2.625GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	2.375		2.625	GHz
中心插损 Insertion Loss (fo)			1.0	dB
带内纹波 Pass Band Ripple			0.8	dB
带外抑制 Rejection	>40dB@DC-1750MHz 3500MHz			dB
耐受功率 Power Handling			10	W
输入驻波 Input VSWR			1.6	:1
输出驻波 Output VSWR			1.6	:1
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	℃
存储温度 Storage Temperature	-40 to +70	℃
接口 Connectors	SMA Female	

外形图Outline Drawing:

Unit:mm;



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-2G5-5-E	Coaxial Band-pass Filter, Passband frequency range: 2.375 to 2.625GHz , Insertion Loss (fo) : 1.0dB, SMA Female	Rev.1.0