

Coaxial Band-pass Filter

3.4-3.6GHz/ SMA Female

Model: TLBF-3G5-200M-E2

TLBF-3G5-200M-E2 is a coaxial band-pass filter with a passband frequency from 3.4 to 3.6GHz and a rejection frequencies at 2.8GHz and 3.9 GHz. The nominal insertion loss of the filter is 1.0dB and the typical rejection is 20 dB.

Features:

- Passband Frequency Range 3.4 to 3.6GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

电气特性 Electrical Characteristics:


参数 Parameter	Min	Typ	Max	单位 Units
通带频率范围 Passband Frequency range	3.4		3.6	GHz
中心插损 Insertion Loss (fo)			1.0	dB
带内纹波 Pass Band Ripple			0.8	dB
带外抑制 Rejection	>20dB@2800MHz 3900MHz			dB
耐受功率 Power Handling			50	W
输入驻波 Input VSWR			1.6	:1
输出驻波 Output VSWR			1.6	:1
阻抗 Impedance	50			Ohms

环境和机械特性 Envirionmental And Physical Characteristics:

类型 Description	参数 Parameter	单位 Units
操作温度 Operating Temperature	-40 To +70	℃
存储温度 Storage Temperature	-40 to +70	℃
接口 Connectors	SMA Female	

外形图 Outline Drawing:

Unit:mm;



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLBF-3G5-200M-E2	Coaxial Band-pass Filter, Passband frequency range: 3.4 to 3.6GHz , Insertion Loss (f _o) : 1.0dB, SMA Female	Rev.1.0