

Coaxial High-pass Filter

20-100 MHz/SMA Female

Model: TLHF-20M-100M-L

TLHF-20M-100M-L is a coaxial High-pass filter with a passband frequency from 20 to 100 MHz and a rejection frequency point at 15 MHz. The maximum insertion loss of the filter is 2.5 dB and the minimum rejection is 30 dB.

Features:

- Passband Frequency Range 20 to 100MHz
- Low Insertion Loss

Applications:

- Instrumentations
- Test Labs
- Sub-assemblies

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	20		100	MHz
Passband Insertion Loss			2.5	dB
Pass Band Ripple			1.3	dB
VSWR			1.6	:1
Rejection@15MHz	30			dB
Power Handling			2	W
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40	mm

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLHF-20M-100M-L	Coaxial High-pass Filter, Passband frequency range: 20-100MHz, Passband Insertion Loss: 2.5dB, SMA Female Coaxial Fixed Termination	Rev.1.1

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.