

Coaxial Band-pass Filter

21-23 GHz/2.92mm Female

Model: TLBF-22G-2G-E

TLBF-22G-2G-E is a coaxial band-pass filter with a passband frequency from 21 to 23 GHz and a rejection frequencies @19 GHz and 25 GHz. The maximum insertion loss of the filter is 1.5 dB and the typical rejection is 50 dB.

Features:

- Passband Frequency Range 21 to 23 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	21		23	GHz
Band Width			2	GHz
Passband Insertion Loss			1.5	dB
Pass Band Ripple			1.2	dB
Rejection	>50dB@19&25Ghz			dB
Power Handling			10	W
VSWR			1.6	:1
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	2.92mm Female	

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-22G-2G-E	Coaxial Band-pass Filter, Passband frequency range: 21-23GHz, Passband Insertion Loss: 1.5dB, 2.92mm Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.