

75-110GHz Low Noise Amplifier

1.0mm(f)/75-110GHz /4.5dB NF/25dB Gain

Model: TLLA75G110G-25-45

TLLA75G110G-25-45 is a W-Band low noise amplifier with a typical small signal gain of 25 dB and a nominal noise figure of 4.5 dB across the frequency range of 75 to 110 GHz. The DC power requirement for the amplifier is +12 VDC. The input and output port configuration offers coax adapter structure with 1.0mm female.

Features:

- Ultra Wide Band: 75-110GHz
- Gain: 25dB Typ
- Noise Figure: 4.5dB Typ
- Unconditional stability

Applications:

- Passive Imaging
- Communication Systems
- Radar Systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	75-110			GHz
增益 Gain		25		dB
噪声系数 Noise Figure		4.5		dB
饱和输出功率 Output Psat		15		dBm
直流电压 DC Voltage		12		V DC
阻抗 Impedance		50		Ohms


机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	1.0mm Female/1.0mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	51.8x41.8x12	mm

绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+15 V
输入功率 RF Input Power	+0dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V

外形图 Outline Drawing: Unit:mm; Tolerance:±0.1mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-10		+65	°C
存储温度 Non-operating Temperature	-45		+85	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA75G110G-25-45	Low Noise Amplifier, 75-110 GHz, Noise Figure:2.0dB,Gain:25 dB Type +12V DC,1.0mm Female	Rev.1.1