

Low Noise Amplifier

4-8GHz/0.6dB NF/40dB Gain/10dBm P1dB

Model: TLLA4G8G-40-06

TLLA4G8G-40-06 is a low noise amplifier with a minimum small signal gain of 40 dB and a maximum noise figure of 0.6 dB across the frequency range of 4 to 8 GHz. The DC power requirement for the amplifier is +12 V DC/200 mA. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 4-8GHz
- Gain: 40dB Min
- Noise Figure: 0.6dB Max
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	4		8	GHz
小信号增益 Small Signal Gain	40	43		dB
噪声系数 Noise Figure			0.6	dB
线性输出功率 Output P1dB	10	13		dBm
输出三阶交调 Output IP3		15		dBc
输入驻波 Input VSWR			2	:1
输出驻波 Output VSWR		1.8	2	:1
直流电压 DC Voltage	8	12	16	V DC
直流电流 DC Supply Current		200		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	SMA Female/SMA Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	44.8*29.2*11	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	+16 V
输入功率 RF Input Power	+0 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



***Heat Sink Required During Operation



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+60	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	10,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA4G8G-40-06	Low Noise Amplifier, 4-8GHz, Noise Figure:0.6dB, Gain:40 dB,P1dB:10dBm,+12V DC,Without Heatsink	Rev.1.0
TLLA4G8G-40-06-HS	Low Noise Amplifier, 4-8GHz, Noise Figure:0.6dB, Gain:40 dB,P1dB:10dBm,+12V DC,With Heatsink	Rev.1.0