

Coaxial Band-pass Filter

14-14.5 GHz/SMA Female

Model: TLBF-14G-14G5-S

TLBF-14G-14G5-S is a coaxial band-pass filter with a passband frequency from 14 to 14.5 GHz and a rejection frequencies @13.75 GHz and 14.75GHz. The maximum insertion loss of the filter is 1.0 dB and the typical rejection is 40 dB.

Features:

- Passband Frequency Range 13.5 to 14 GHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	14		14.5	GHz
Passband Insertion Loss			1.0	dB
Rejection	≥40dBc@13.75&14.75GHz			dB
Power Handling			10	W
VSWR			1.5	:1
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-55 To +85	°C
Connectors	SMA Female	
Weight	/	g

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-14G-14G5-S	Coaxial Band-pass Filter, Passband frequency range: 14-14.5GHz, Passband Insertion Loss: 1.0dB, SMA Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.