

Coaxial Band-pass Filter

155-245 MHz/SMA Female

Model: TLBF-200M-90M-L

TLBF-200M-90M-L is a coaxial band-pass filter with a passband frequency from 155 to 245 MHz and a rejection frequencies at $f_c \pm 60$ MHz. The maximum insertion loss of the filter is 3.2 dB and the minimum rejection is 40 dB.

Features:

- Passband Frequency Range 155 to 245 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	155		245	MHz
Band Width			90	MHz
Insertion Loss(f_0)			3.2	dB
Pass Band Ripple			3.0	dB
VSWR			1.6	:1
Rejection@ $f_c \pm 60$ MHz	40			dB
Power Handling			2	W
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temperature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40.4	mm

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-200M-90M-L	Coaxial Band-pass Filter, Passband frequency range:155-245MHz, Insertion Loss(f0):3.2dB, SMA Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.