

Coaxial Band-pass Filter

750-1250 MHz/SMA Female

Model: TLBF-750M-1250M-L

TLBF-750M-1250M-L is a coaxial band-pass filter with a passband frequency from 750 to 1250 MHz and a rejection frequencies point at 550 MHz and from 1450 to 1960 MHz..The maximum insertion loss of the filter is 1.3 dB and the minimum rejection is 50 dB.

Features:

- Passband Frequency Range 750 to 1250 MHz
- Low Insertion Loss
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	750		1250	MHz
Band Width			500	MHz
Passband Insertion Loss			1.3	dB
Pass Band Ripple			1.8	dB
VSWR			1.6	:1
Rejection@550MHz&1450-1960MHz	50			dB
Power Handling			2	W
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40.4	mm

Outline Drawing:

Unit:mm




ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-750M-1250M-L	Coaxial Band-pass Filter, Passband frequency range: 750-1250MHz, Passband Insertion Loss: 1.3dB, SMA Female	Rev.1.0

Typical Performance Data:



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.