

Coaxial Band-pass Filter

1350-1440 MHz/SMA Female

Model: TLBF-1350M-1440M-L

TLBF-1350M-1440M-L is a coaxial band-pass filter with a passband frequency from 1350 to 1440 MHz and a rejection frequencies from DC to 1300 MHz and point at 1500 MHz. The maximum insertion loss of the filter is 2.8 dB and the minimum rejection is 15 dB.

Features:

- Passband Frequency Range 1350 to 1440 MHz
- High Rejection
- Steep Rejection Skirts

Applications:

- Instrumentations
- Radar Systems
- System Integrations

Electrical Characteristics:


Parameter	Min	Typ	Max	Units
Passband Frequency range	1350		1440	MHz
Passband Insertion Loss			2.8	dB
Pass Band Ripple			2.6	dB
VSWR			1.6	:1
Rejection@DC-1300MHz&1500MHz	15			dB
Power Handling			2	W
Impedance	50			Ohms

Envrionmental And Physical Characteristics:

Description	Parameter	Units
Operating Temerature	-40 To +70	°C
Connectors	SMA Female	
Size	10*12*40	mm

Outline Drawing:

Unit:mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Ordering Information:

Base Number	Description	Revision
TLBF-1350M-1440M-L	Coaxial Band-pass Filter, Passband frequency range: 1350-1440MHz, Passband Insertion Loss: 2.8dB, SMA Female	Rev.1.0