

Power Amplifier

8-12GHz/45dB Gain/45dBm Psat

Model: TLPA8G12G-45-45

TLPA8G12G-45-45 is a power amplifier with a minimum power gain of 45 dB and a typical Psat of 45 dBm across the frequency range of 8 to 12 GHz. The DC power requirement for the amplifier is +28 VDC/1.7 A. The input and output port configuration offers coax adapter structure with SMA female.

Features:

- Frequency range: 8-12GHz
- Gain: 45dB Min
- Output Power Psat: 45dBm Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Cellular
- PCN
- GSM
- ISM
- Lab Test

Electrical Characteristics:

Parameter	Min	Typ	Max	Units
Frequency range	8		12	GHz
Power Gain	45			dB
Gain Flatness		±3		dB
Output Psat		45		dBm
Spurious@Pout=45dBm			-60	dBc
Harmonic@Pout=45dBm			-30	dBc
Input VSWR		1.5		:1
DC Voltage		28		V DC
DC Current		1.7		A
Impedance		50		Ohms

Mechanical Specifications:

Parameter	Value	Units
Input /Output Connector	SMA Femlae/SMA Female	
DC Bias	Feedthru capacitors	
Size	60*60*11(Without heatsink) 165.4*90*101(With heatsink)	mm
Weight	≤200	g




Absolute Maximum Ratings:

Parameter	Value
Supply Bias Voltage	+29 V
RF Input Power	+5 dBm
ESD sensitivity (HBm)	Class 0, passed 150V



Outline Drawing:

Unit:mm; Tolerance:±0.1mm



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

Environmental Conditions:

Parameter	Min	Typ	Max	Units
Operating Temperature*	-40		+50	°C
Non-operating Temperature*	-50		+60	°C
Relative humidity		95		%
Altitude	10,000			feet
Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			


*Note: For a wider temperature range, please consult the manufacturer.

Ordering Information:

Base Number	Description	Revision
TLPA8G12G-45-45	Power amplifier 8-12GHz, Gain:45dB,Psat:45dBm,+28V DC,Without Heatsink	Rev.1.2
TLPA8G12G-45-45-HS	Power amplifier 8-12GHz, Gain:45dB,Psat:45dBm,+28V DC,With Heatsink	Rev.1.2

Typical Performance Data:


Input VSWR vs Frequency




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Small Signal Gain vs Frequency



P1dB vs Frequency




Pout@Pin




Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.

Typical Performance Data:


Psat vs Frequency



Spurious vs Frequency



Harmonic vs Frequency



Note: Above data is for ref only, actual data may vary from unit to unit depending on operating environment and other factors like material lots etc.