

Low Noise Amplifier

26.5-50GHz/6.0dB NF/18dB Gain/14dBm P1dB

Model: TLLA26.5G50G-18-60

TLLA26.5G50G-18-60 is a low noise amplifier with a typical small signal gain of 18 dB and a nominal noise figure of 6.0 dB across the frequency range of 26.5 to 50 GHz. The DC power requirement for the amplifier is +12 V DC/200 mA. The input and output port configuration offers coax adapter structure with 2.4mm female.

Features:

- Frequency range: 26.5-50GHz
- Gain: 18dB Typ
- Noise Figure: 6.0dB Typ
- Good Power and Gain Flatness
- 50 Ohm Matched Input / Output

Applications:

- Communication systems

电气特性 Electrical Characteristics:

参数 Parameter	Min	Typ	Max	单位 Units
频率范围 Frequency range	26.5		50	GHz
小信号增益 Small Signal Gain	15	18		dB
增益平坦度 Gain Flatness		±2.0	±3.0	dB
噪声系数 Noise Figure		6.0		dB
线性输出功率 Output P1dB		14		dBm
杂散Spurious		-60		dBc
三阶交调 IP3		20		dBm
输入驻波 Input VSWR		1.8	2.0	:1
输出驻波 Output VSWR		1.8	2.0	:1
直流电压 DC Voltage		+12		V DC
直流电流 DC Supply Current		200		mA
阻抗 Impedance	50			Ohms

机械特性 Mechanical Specifications:

参数 Parameter	指标 Value	单位 Units
输入/输出接口 Input /Output Connector	2.4mm Female/2.4mm Female	
直流偏置 DC Bias	Solder Pin	
尺寸 Size	30*30*8	mm


绝对最大值 Absolute Maximum Ratings:

参数 Parameter	指标 Value
供电偏置电压 Supply Bias Voltage	TBD
输入功率 RF Input Power	+5 dBm
ESD灵敏度 ESD sensitivity (HBm)	Class 0, passed 150V



外形图 Outline Drawing:

Unit:mm; Tolerance:±0.1mm



*****Heat Sink Required During Operation**



ESD Protection: Strictly adhere to ESD precautions to prevent electrostatic damage.

温度环境 Environmental Conditions:

参数 Parameter	Min	Typ	Max	单位 Units
操作温度 Operating Temperature	-40		+75	°C
存储温度 Non-operating Temperature	-55		+125	°C
相对湿度 Relative humidity		95		%
海拔 Altitude	50,000			feet
震动 Shock / Vibration(MIL-STD-810F)	25g rms (15 degree 2KHz) endurance, 1 hour per axis			
冲击 Shock(non operating)	20G for 11msc half sin wave,3 axis both directions			

订货信息 Ordering Information:

标准型号 Base Number	描述 Description	版本号 Revision
TLLA26.5G50G-18-60	Low Noise Amplifier, 26.5-50GHz, Noise Figure:6.0dB, Gain:18dB,P1dB:14dBm,+12V DC,Without Heatsink	Rev.1.1
TLLA26.5G50G-18-60-HS	Low Noise Amplifier, 26.5-50GHz, Noise Figure:6.0dB, Gain:18dB,P1dB:14dBm,+12V DC,With Heatsink	Rev.1.1